

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



DE 020009  
25 apr

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : H04R 7/20, F16F 1/26		A1	(11) International Publication Number: WO 99/66763
			(43) International Publication Date: 23 December 1999 (23.12.99)
(21) International Application Number: PCT/IB99/01016 (22) International Filing Date: 3 June 1999 (03.06.99) (30) Priority Data: 98202005.9 16 June 1998 (16.06.98) EP (71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (71) Applicant (for SE only): PHILIPS AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE). (72) Inventor: D'HOOGH, Guido, O., M.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). (74) Agent: SCHRJNEMAEKERS, Hubert, J., M.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).		(81) Designated States: JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: DEVICE HAVING TWO COAXIALLY DISPOSED BODIES WHICH ARE MOVABLE RELATIVE TO ONE ANOTHER ALONG A TRANSLATION AXIS

(57) Abstract

A device comprising two bodies (3, 5) which are disposed coaxially with respect to a translation axis (1) and comprising a comparatively compact suspension means via which at least one of the bodies is movable with respect to the other body along the translation axis. The suspension means, which allows comparatively large and accurately defined axial excursions of the one body with respect to the other body, comprises a set of at least three blade spring elements (7) which are positioned around the translation axis. These blade spring elements each comprise two blade springs (7a, 7b) which are inclined with respect to a plane (XY) oriented perpendicularly to the translation axis, the blade springs of each blade spring element, the blade springs of each blade spring element each having two peripheral portions (7a1, 7a2; 7b1, 7b2) which each extend parallel to the plane which is oriented perpendicularly to the translation axis. One of the blade springs is connected to the one body near one of its peripheral portions and the other blade spring is connected to the other body near one of its peripheral portions, while the blade springs of each blade spring element are interconnected near their other peripheral portions.

